

GMG

Global Machinery Group, Inc.

6094-RT

ULTRA-DECK ROUGH TERRAIN SCISSOR LIFT



STANDARD FEATURES:

- Auto Leveling Outriggers
- 24'10" (7.55m) platform extended
- Dual deck extensions
- Material loading, Front/Rear
- Fully proportional Drive/Lift
- GMG 4wd with Traction Control
- Oscillating axle
- Solid cushion tires
- Kubota diesel engine with slide-out module
- Variable engine speed
- Quiet mode operation

Options, refer to back page



MODELS 6094

Measurements	US	Metric
Working height maximum	66'	20.1 m
Platform height maximum	60'	18.2 m
Platform height - stowed platform floor	6'7"	2.02 m
Platform length - retracted - extended	17'5" 24'10"	5.23 m 7.55 m
Platform width - outside	75"	1.9 m
Toeboard height	6"	0.15 m
Height - stowed rails lowered	128" 97"	3.25 m 2.46 m
Length stowed	17' 5"	5.23 m
Width	94"	2.38 m
Wheelbase	113"	2.87 m
Ground clearance - center	15"	38 cm

Productivity

Maximum platform occupancy	4	
Lifting capacity	1,200 lbs	540 kg
Extension deck capacity (each deck)	500 lbs	227 kg
Drive height	40'	12 m
Gradeability - stowed	45%	
Turning radius - inside	82" / 2.08 m	
Turning radius - outside	16.8' / 5.12 m	
Raise speed	60 seconds	
Lower speed	55 seconds	
Controls	fully proportional	
Drive	four wheel	
Drive speed, stowed	4.5 mph	7.2 km/h
Drive speed, elevated	0.25 mph	0.4 km/h
Tires - rough terrain	33 x 12 in	84 x 30 cm

Power

Power source	Kubota Diesel Engine	
Fuel tank capacity	25 gal / 95.0 L	
Hydraulic system capacity	40 gal / 115.0 L	

Weight

Standard	20,450 lbs	9276 kg
----------	------------	---------

STANDARD FEATURES

- Auto Leveling Outriggers
- Solid RT Tires
- Movable upper control station
- Machine tie-downs
- Hour meter
- Dual 12v batteries
- Platform swing gates
- Flashing beacon (1)

Work Area

- 24' 10" (7.55m) platform, extended
- Dual deck extensions
- Lanyard attachments
- Material loading, front/rear

Performance

- Fully proportional drive / lift controls
- GMG 4wd with traction control
- Oscillating axle

Power

- Kubota diesel engine with slide-out module
- Variable engine speed
- Engine quiet mode

Safety

- Emergency shut-off at platform and lower controls
- Non-skid platform deck
- Decent alarm
- Self-closing swing gates
- Multi-axis tilt sensor
- Scissor maintenance lock
- Emergency lowering system
- Automotive horn

Serviceability

- Easy maintenance access to mechanical, electrical, and hydraulic components

OPTIONAL FEATURES

- Reflective tape kit
- Flashing beacons (4) mounted on each outrigger
- Platform work lights (4)
- Drive lights (4) mounted on front/back of chassis
- Generator 3.5kw
- Control box cover, upper
- Cooler, hydraulic
- Tool cabinet, lockable mounted on lower module
- Tool tray mounted on guardrails
- Fire extinguisher kit (2), 6kg on chassis, 2kg on platform
- Diesel scrubber
- Non-marking tires

GMG Corporate Office

3428 Bullock Lane
San Luis Obispo, CA 93401

Phone: +1.805.303.2066

Toll Free (USA/Canada): +1.800.301.0499

Distributed By:



www.goGMG.com